

EPDM Rubber General Purpose Air & Water Hose

General Applications:

- Agricultural
- Construction
- Industrial
- Water service lines

Construction:

- **Tube** – Black EPDM, limited oil resistance.
- **Reinforcement** – Spiral polyester yarn.
- **Cover** – Black or red abrasion and ozone-resistant EPDM, limited oil resistance.

Service Temperature Range:

-40°F (-40°C) to +212°F (+100°C)

Features and Advantages:

- Long lengths on reels.

Branding:

GP AIR & WATER – SIZE – WP – MADE IN USA



Packaging:

Maximum 2 pcs. on reel.

1/4" – 3/4" ID hoses supplied on plastic reels.

1" – 2" ID hoses supplied on wooden reels.

Note: For Quick Disconnect Couplings and Worm Gear Clamps refer to pages 15, 18-19 of this catalog.

Nominal Specifications

Part Number	Color	ID (in)	OD (in)	Working Pressure (psi)	Reel Length (ft)	Weight (lbs/pc)
BEGP-025X700	Black	1/4	0.50	250	700	84
REGP-025X700	Red	1/4	0.50	250	700	84
BEGP-031X700	Black	5/16	0.59	200	700	77
REGP-031X700	Red	5/16	0.59	200	700	84
BEGP-038X700	Black	3/8	0.69	250	700	112
REGP-038X700	Red	3/8	0.69	250	700	119
BEGP-050X700	Black	1/2	0.84	250	700	168
REGP-050X700	Red	1/2	0.84	250	700	175
BEGP-062X700	Black	5/8	0.94	200	700	203
REGP-062X700	Red	5/8	0.94	200	700	210
BEGP-075X700	Black	3/4	1.16	250	700	252
REGP-075X700	Red	3/4	1.16	250	700	266
BEGP-100X700	Black	1	1.38	200	700	343
REGP-100X700	Red	1	1.38	200	700	357
BEGP-125X300	Black	1 1/4	1.78	200	300	237
REGP-125X300	Red	1 1/4	1.78	200	300	243
BEGP-150X300	Black	1 1/2	2.00	200	300	270
REGP-150X300	Red	1 1/2	2.00	200	300	285
REGP-200X250	Red	2	2.50	200	250	339

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.